# Vanity basins - TF042BI


**C€** EN 14688:2006

#### Cod. TF042BI


Basin  $\emptyset$  42 h14 cm. Sit-on installation. Fixing kit included. Weight 8,5 Kg.







	Wall mounted taps	Taps mounted on counter top
A:	40	95
B:	250	305
C:	460	515
D:	420	475





BATAFORM®



CERASLIDE®



Riflessi di Luce



Bagno di Colore Bianco opaco

\* For taps mounted on counter top

## Cod. FI024BI

Valve drain with ceramic top for basins without overflow. Weight 0,5 Kg



#### Cod. FI024CR

Chromed valve drain for basins without overflow. Weight 0,5 Kg









# Tips for proper cleaning Ceramic cleaning

We recommend the use of warm water in combination with non-abrasive cleaning products

### Click to view or download



**DOP N° L001-01** 



Is the result of years of research, on the glazes and the ceramic application, that ensures more protection, more resistance and ease of cleaning. The careful control of temperatures in the various cooking stages, in a cycle that can last up to 26 hours, ensures perfect homogeneity of the product during the sintering process, reducing porosity and guaranteeing greater resistance against stains, dirt and abrasions.



The antibacterial bataform treatment was developed to ensure deeper hygiene, basing its effectiveness on the reaction of silver ions, which inhibit the proliferation of bacteria. tests carried out by certified laboratories, according to the uni4543 standard, have confirmed a drastic decrease in the presence of bacteria, without however altering the glossy glaze. for cleaning operations, follow the recommendations given for the ceraslide glaze.